

SCHEDULE B

Fuel Specifications

PRODUCT and QUALITY SPECIFICATION

RESIDUAL FUEL OIL NO.6

| <i>Test</i> | <i>Units</i> | <i>Method</i> <i>ASTM D-</i> | <i>Specification Limits</i> | |
|------------------------|--------------|---------------------------------|-----------------------------|-------------|
| | | | <i>LSFO</i> | <i>HSFO</i> |
| API Gravity @ 60°F | °API | 287-00 | 14.0 – 21.0 | 14.0 – 21.0 |
| Viscosity @ 100°F | SSU | 445/2161 | 1500 Max. | 1500 Max. |
| Flash Point | °C | 93-02a | 66 Min. | 66 Min. |
| Fire Point | °C | 92-02a | 94 Min. | 94 Min. |
| Pour Point | °C | 97-05a | +21 Max. | +21 Max. |
| Water by Distillation | vol % | 95-05e | 0.50 Max. | 0.50 Max. |
| Sediment by Extraction | wt % | 473-02 | 0.50 Max. | 0.50 Max. |
| Sulfur Content | wt % | 4294-03 | 1.19 Max. | 2.00 Max. |
| Ash Content | wt % | 482-03 | 0.100 Max. | 0.100 Max. |
| Micro-Carbon Residue | wt % | 189-01 | 15.0 Max. | 15.0 Max. |
| Vanadium Content | ppm | 5708 | 80 Max. | 80 Max. |
| Aluminum Content | ppm | 5184 | Report | Report |
| Silicon Content | ppm | 5184 | Report | Report |
| Al + Si | ppm | Calculate | 80 Max. | 80 Max. |
| Gross Heating Value | MBTU/ bbl | 240-00 | 6.10 Min. | 6.10 Min. |

Notes: LSFO = Low Sulfur Fuel Oil
 HSFO = High Sulfur Fuel Oil